SOPRA N°2



Product Data Sheet

Sopra N°2 clearly inaugurates a new era for the "Premium High End" bringing new performance criteria. Compact, modern, a pure design, character... all these are essential factors to ensure perfect integration into your interior. Equipped with best midrange drivers ever developed by Focal, with the NIC (Neutral Inductance Circuit) and TMD (Tuned Mass Damper) technologies, Sopra N°2 pushes back the limits of sound reproduction in terms of transparency in a very compact enclosure. Sopra N°2 is perfectly at ease in rooms measuring up to 320ft2 (30m²), and is even ideal for larger rooms measuring up to 750ft2 (70m²).



Key points

- New midrange driver with TMD suspension and NIC magnetic circuit
- New IHL Beryllium tweeter (Infinite Horn Loading)
- Drivers developped and manufactured by Focal in France

Туре	Three-way Bass-reflex floor standing loudspeaker
Drivers	Two 7" (18cm) "W" woofer 6 ^{V2} " (16.5cm) "W" midrange with TMD suspension, NIC motor 1 ^{V16} " (27mm) IHL Beryllium inverted dome tweeter
Frequency response (+/- 3dB)	34Hz - 40kHz
Low frequency point - 6dB	28Hz
Sensivity (2.83V / 1m)	91dB
Nom. impedance	8 Ohms
Minimum impedance	3.1 Ohms
Crossover frequency	250Hz / 2 200Hz
Recommended amplifier power	40 - 300W
Dimensions (HxLxP)	46 ^{27/32} x14 ^{3/32} x21 ^{17/64} " (1 190x358x540mm)
Net weight	122lbs (55kg)





Lacquered standard finishes (face + side panels)

Standard Oak finishes

